

CNC Vertical Boring & Turning Mills

# ***VTB/VTC Series***

**VTB-100T/100/125/140/160/125E/140E/160E/200E/250E**  
**VTC-100/125/140/160/125E/140E/160E/200E/250E**





# ***VTB/VTC Series***

***100T/100/125/140/160/125E/140E/160E/200E/250E***

***Heavy Duty, High Precision, Vertical Boring and Turning Mills  
Designed to Deliver Superior Performance***

## ■ **High Productivity**

- Maximum 1250 to 3000mm turning capacity
- Maximum 4 to 15 tons load capable table
- Elevating cross rail of 700 and 1000mm travel
- Full controlled C-axis and rotary spindle (only for VTC)
- Automatic tool changing system up to 12/24 (VTB/VTC) tools

## ■ **High Reliability**


- Heavy duty, wide guide ways of box type
- Massive one-piece cast iron bed, column, saddle, and cross-rail
- Induction-hardened and precise-ground guide ways
- Extra large 220, 240 and 280mm square spheroidal-graphite-iron ram
- The saddle enclosing the ram is one-piece casting to keep the high rigidity.

## ■ **High Accuracy**


- Qualified precision bearings & ball screws
- Fluoroplastic-bonded & hand-scraped guide ways
- Full automatic lubrication to all critical areas









Turning



Face milling




End milling




Drilling






**Bed**




The stress analysis was applied to the bed structure design for maintaining the best condition to support the heavy load and cutting force and to minimize the distortion, deflection and dampen vibration.

**Table & Spindle Bearings**




- Heavy duty table and large diameter high precision spindle bearings guarantee heavy loads and precise machining.
- Heavy duty 4-jaw independent chuck is standard (max. clamping force 4 metric tons). Hydraulic power chuck and automatic pallet changer system are available.
- The main spindle and drive gears are made of special alloy steel. They are induction hardened, fully stress relieved, and then precision ground for maximum performance.
- The power is transmitted to the table through the automatically shifted two speed gear box which generates enough speed and torque to satisfy wide spectrum of most demanding machining requirement.
- Helical gears are used for smooth and efficient power transmission characteristics.
- High-accurate table index by C-axis control: 0.001° on model VTC.
- Forced lubrication system provided.

**Machine Construction**




The column, cross rail, bed, saddle, and table are constructed of high quality Meehanite cast iron. These main components are densely ribbed, thick walled, and fully stress relieved for long lasting accuracy.

**Motor & Table Gear**




A direct connection of drive gear train to the motor minimize the loss of torque.






### ■ Saddle & Ram

- The saddle enclosing the ram is one-piece casting to keep the high rigidity.
- Huge 220, 240 and 280mm square spheroidal graphite iron ram, hardened and ground, is encased in the heavily ribbed saddle and is hydraulically counter balanced.
- Low friction fluoroelastic resin bonded to the ram sliding surfaces of the saddle minimizes friction.
- Model VTC has milling spindle with high-speed that involves drilling, milling, and tapping.
- Pull stud tool mounting and dismounting way of machining center type (P50T-I / DIN. 69872.50).
- Automatic metered lubrication system ensures lasting accuracy.
- Tool fall-safety device assures safe operation.




### ■ Elevating Cross Rail (VTB/VTC-E)

Vertical positioning of this massive cross rail is hydraulically powered. Positioning accuracy is assured by automatically actuated precision pins and 37.4 tons of hydraulic clamping force.



### ■ Automatic Tool Changer

The standard 12 tool capacity (24 tools for model VTC) automatic tool changer system and a wide variety of available tooling enable uninterrupted fully automatic machining possible. This rigidly constructed carousel type tool changer features high speed random indexing and is capable of safely handling tools of up to 50kg (110 pounds).



### ■ Guide Ways

The wide box type guide ways are induction-hardened and precision-ground. Mating surfaces of the sliding components are coated with fluoroelastic resin and are hand scraped for perfect fit. Fully automatic metered lubrication system provided.


### ■ Axis Drives

Each axis is driven by a high precision ballscrew and is powered by a high torque, maintenance free Fanuc digital AC servo motor. Ballscrews are supported on both ends by high precision bearings. The optional X axis linear scale feed back system combined with double anchor pretensioned design assures outstanding machining accuracy and repeatability. Rapid traverse rate of both X & Z axes is 7500mm/min (295 ipm).




### Table Torque & Power Diagram


#### VTB-100




#### VTB-125 VTB-140




#### VTB-160



#### VTB-200E




#### VTB-250E




— 30min Operating Zone  
- - - Continues Operating Zone

### Ram Head Cutting Capability




### Machining Range



Unit:mm

	VTB/VTC					
	100	125(E)	140(E)	160(E)	200E	250E
A	1000	1250	1400	1600	2000	2500
B	1250	1600	1600	2000	2500	3000
C	800	900 (1400)		2000	2000	2000
D	1300	1600	1600	1900	1500	1700
E	-	(700)		1000	1000	
F	800	900		1500	1600	

### Minimum Boring



( ): 200E/250E

## Machine Specifications

Items		Unit	VTB/VTC							
			100T	100	125 125E	140 140E	160 160E	200E	250E	
Capacity	Max. turning diameter	mm (inch)	1250(49.2)		1600(63)		2000(78.7)	2500(98.4)	3000(118)	
	Max. turning height	mm (inch)	800(31.5)		900(35.4)		1400(55.1)	2000(78.7)	2000(78.7)	
	Max. torque	N·m (lbf.ft)	12005(8860)		17885(13200)	20433(15100)	23863(17600)	40403(29800)	55010(40650)	
	Max. cutting force	kgf (lbs)	2000(4410)		3000(6615)		3000(6615)	5000(11020)	5000(11020)	
	Max. workpiece weight	kg (lbs)	4000(8820)		8000(17640)		10000(22100)	12000(26000)	15000(33000)	
Table	Table diameter	mm (inch)	1000(39.4)		1250(49.2)	1400(55.1)	1600(63)	2000(79)	2500(98.4)	
	Table speed	rpm	1.1~450		0.9~360	0.8~320	0.7~280	1~200	1~150	
	Table speed range	step	Auto. 2-step							
C-axis (VTC)	Min. index angle	deg.	0.001°							
	Cutting feedrate	deg/min	0~1200				0~900			
	Max. speed	rpm	3.333				2.5			
Ram Head	Tool size	mm (inch)	□ 32(□1 1/4)						□ 50(□2)	
	Spindle taper	-	ISO 7/24 No.50							
	Mill spindle speed	rpm	30~3000						15~1500	
	Max. mill spindle torque	N·m (lbf.ft)	-	186(137)	235(173)			280(206)	280(206)	
	Ram cross section	mm (inch)	220×220(8.66×8.66)					240×240(9.4×9.4)	280×280(11×11)	
Travel & Feedrate	X-axis travel(Saddle horizontal)	mm (inch)	1390(55)	1300(51)	1600(63)		1900(75)	1500(59.1)	1700(67)	
	Z-axis travel(Ram Vertical)	mm (inch)	800(31.5)		900(35.4)		900(35.4)	1500(59.1)	1600(63)	
	Vertical travel of cross rail	mm (inch)	-		700(27.5)			1000(39.4)		
	X/Z-axis cutting feedrate	mm/min (ipm)	Max.7500(295)						Max.10000(394)	
	X/Z-axis rapid traverse	mm/min (ipm)	7500(295)						10000(394)	
	Cross rail rapid traverse	mm/min (ipm)	-		300(12)			300(11.8)		
ATC	Type of tool holder	-	MAS BT50							
	Tool magazine capacity	VTB	Turning 6-tool : VTB-100T, Turning 12-tool : VTB-100/125/140/160/200E/250E							
		VTC	16-tool (Turning 8, Milling 8) : VTC-100 24-tool (Turning 12, Milling 12) : VTC-125/140/160/200E/250E							
	Max. tool weight	kg (lbs)	50(110)				50(110)	70(110)		
Type of pull stud	-	P50T-I : VTB/DIN.69872.50 : VTC								
Motor	Table motor	kW (Hp)	AC 30/37(40/50)		AC 37/45(50/60)		AC 45/55(60/73)	AC 60/75(80/100)		
	Mill spindle motor	(Cont./30min)	-	AC 11/15	AC 15/18.5(20/25)		AC 18.5/22(25/30)	AC 22/26(30/35)		
	C-axis motor	kW (Hp)	-	AC 4(5.3)	AC 7(9.3)		AC 9(12)	AC 9(12)		
	X/Z-axis servo motor	kW (Hp)	AC 4(5.3)		AC 7(9.3)		AC 7(9.3)	AC 9/4(2 set)		
Power Source	Input power supply	-	AC 200/220V ±10%, 50/60Hz ±1%							
	Power capacity(VTB/VTC)	kVA	65/70		75/80		150	200		
Machine Size	Floor space	-	Refer to page 14							
	Weight	kg (lbs)	18000 (39700)	18500 (40800)	19000/25800 (41900/56900)	24300/26100 (53600/57500)	28800/30900 (63500/68200)	61700 (136000)	78000 (172000)	
CNC Controller		-	FANUC 32i-A							

### Standard Accessories

- CNC controller, FANUC 32i-A
- Table and servo drives and motors
- 4-jaw independent chuck
- Automatic tool changer system
- Lubrication oil cooler
- C-axis scale (Only for VTC)
- Hydraulic power unit
- Automatic lubrication system for guides
- Coolant system and Washer coolant
- Through tool coolant
- Through spindle coolant (Only for VTC)
- Splash guard and safety guard rail
- X-axis slideway protect steel cover
- Work light
- Patrol lamp (Red, Yellow, Green)
- NC power off
- Chip pan
- Levelling blocks
- Foundation bolts and nuts
- Tool box with maintenance tools

### Optional Accessories

- APC type (2-pallet, 3-station)
- Hyd. 3-jaw & manual 4-jaw combination chuck (Ø1000, 1250, 1400, 1600, 2000mm)
- Chip conveyor & bucket
- Scale feedback (X/Z-Axis)
- Tool setter
- Work probe
- High pressure coolant system
- Air-conditioner for electrical cabinet
- High cooler for operation panel
- Transformer
- A.V.R
- Tool holders



## ■ CNC System Specifications (FANUC 32i-A)

### Standard Function

#### Controlled Axis

Controlled axes	3 axes(X, Z, C)
Simultaneously controlled axes	2 axes
Increment system	0.001mm(0.0001")
HRV2 control	
Flexible feed gear	Optional DMR
Interlock	All/each axis, each direction, block start, cutting block start
Machine lock	All/each axis
Emergency stop	
Over travel	
Stored stroke check 1	
Mirror image	All/each axis
Follow-up	
Servo off/mechanical handle	
Chamfering on/off	
Inch / Metric conversion	

#### Operation

Automatic operation	
MDI operation	
DNC operation with memory card	CF Card
Program number search	
Sequence number search	
Wrong operation prevention	
Buffer register	
Dry run	
Single block	
Manual continuous feed(jog)	
Manual reference position return	
Reference position setting without DOG	
Reference position return speed set	
Reference position shift	
Incremental feed	x1, x10, x100
Program restart	
Manual handle feed 1-unit	1-unit
Handle interruption	

#### Auxiliary/Spindle Functions

Auxiliary function	M8 digit
Auxiliary function lock	
High-speed M/S/T/B interface	
Spindle speed function	S5 digit, binary output
Rigid tap	



#### Interpolation Functions

Nano interpolation	
Positioning	G00
Exact stop mode	G61
Tapping mode	G63
Cutting mode	G64
Exact stop	G09
Linear interpolation	
Circular interpolation	
Dwell	
Thread cutting, synchronous cutting	
Multi threading	
Continuous threading	
Skip	G31
Torque limit skip	
Reference position return	G28
Reference position return check	G27
2nd reference position return	G30

#### Feed Functions

Rapid traverse rate	MAX 999.999 m/min(1um)
Rapid traverse override	F0, 25, 50, 100%(1step)
Feed per minute	G98 mm/min
Feed per revolution	G99 mm/rev
Tangential speed constant control	
Cutting feedrate clamp	
Automatic acceleration/deceleration	Rapid traverse: linear Cutting feed: exponential, linear
Rapid traverse bell-shaped acceleration/deceleration	
Feedrate override	0-254%
Jog override	0-655.34%
Override cancel	
Manual per revolution feed	
Linear acc/dec after cutting feed interpolation	

#### Program Input

Tape code	EIA / ISO
Label skip	
Control in/out	
Optional block skip	1
Max. programmable dimension	±9 digit
Program file name	32 characters
Sequence number	N8 digit
Absolute/incremental programming	Combined use in the same block

Decimal point programming/pocket calculator type	
decimal point programming	
Input unit 10 time multiply	
Diameter/radius programming	
Plane selection	G17, G18, G19
Automatic coordinate system setting	
Manual absolute on and off	
G code system	A
Programmable data input	G10
Programmable parameter input	
Sub program call	10 folds nested
Canned cycle	
Circular interpolation by R programming	R, I, J, K 12digit
Coordinate system shift	
Direct input of coordinate system shift	
Chamfering/corner R	

#### Tool Function/Tool Compensation

Tool function	
Tool offset pairs	32-pairs
Tool offset	
Tool offset value counter input	
Direct input of tool offset value measure	
Tool geometry/wear Compensation	

#### Accuracy Compensation Function

Backlash compensation	
Backlash compensation for each rapid traverse and cutting feed	
Stored pitch error compensation	

#### Editing Operation

Part program storage size	512 Kbyte(1280m)
Number of registerable programs	63
Part program editing	
Program protect	
Extended Part program editing	
Memory card program edit & operation	
Background editing	

#### Setting and Display

Status display	
Lock function	
Current position display	
Program comment display	31 characters
Parameter setting and display	
Alarm display	
Alarm history display	
Operation history display	
Actual cutting feedrate display	
Servo setting screen	
Servo waveform display	
Maintenance information screen	
Multi-language display	
Data protection key	4 type
Self-diagnosis function	
Run hour and parts count display	

#### Data input/output

External key input	
External workpiece number search	9999
Memory card input/output	
Screen hard copy	
Automatic data backup	
External data input	
RS-232C	

#### Others

MDI/display unit	15" color LCD
------------------	---------------


### Optional Function

#### Optional Functions


Stored stroke check 2, 3	
DNC operation	
Retraction for Rigid tapping	
High speed program check	
Single direction positioning	G60
Helical interpolation	Circular interpolation plus max. 2 axes linear interpolation
Variable lead thread cutting	
Polygon turning	
3rd / 4th reference point return	
Programmable mirror image	
MANUAL GUIDE i	
Spindle orientation	1 spindle
Tool offset pairs	64/99/200/400 pairs
Tool pair for tool management function	64/240/1000 tools
Part program storage size	1/2/4/8 Mbyte
Number of registerable programs	Max.1000 programs
Play back	
Remote diagnostic	
Multi-language display	German/french spanish/italian/chinese
Reader / punch interface	Ch.2
Embedded ethernet	



## ■ Accessories




Automatic Tool Changer




Tool Setter




Work Probe




Automatic Pallet Changer(2 pallets)




Hydraulic Chuck




Automatic Index Chuck  
(for machining large valve)



Automatic Index Chuck  
(for machining small valve)



Electrical V-6 Turret(VTB-100T only)



Capto Tool Holder (C6)



Grinding Attachment




C-axis Brake



■ Tool Holders(Option)


VTB(C)-100/125/140/160/200



● Square tool holder

( ) : 200E


Model	A	B	H	Tool Size
TA12B41000-0060 (TE20A41000-0060)	160	100	306.8	□32(□11/4)
TA12B41000-0061 (TE20A41000-0061)	200	140	346.8	□32(□11/4)
TA12B41000-0062 (TE20A41000-0062)	250	190	396.8	□32(□11/4)



● Square tool holder (Through tool coolant)


( ) : 200E

Model	A	B	H	Tool Size
TA12C41000-0160 (TE20A41000-0160)	160	100	306.8	□32(□11/4)
TA12C41000-0161 (TE20A41000-0161)	200	140	346.8	□32(□11/4)
TA12C41000-0162 (TE20A41000-0162)	250	190	396.8	□32(□11/4)




● Side lock holder

Model	A	H	D	Tool Size
TA12B41000-5350	110	256.8	∅ 55	∅ 25 (∅ 1)
TA12B41000-5360	110	256.8	∅ 62	∅ 32 (∅ 1 1/4)
TA12B41000-5370	160	306.8	∅ 70	∅ 40 (∅ 1 1/2)
TA12B41000-5380	160	306.8	∅ 90	∅ 50 (∅ 2)




● Morse taper holder(MS type)

Model	A	H	D	Tool Size
TA12B41000-5450	110	256.8	∅ 85	MT No.5
TA12B41000-5460	160	306.8	∅ 100	MT No.6




● Morse taper holder(ML type)

Model	A	H	D	Tool Size
TA12B41000-5550	240	386.8	∅ 85	MT No.5
TA12B41000-5560	290	436.8	∅ 100	MT No.6




● Boring tool holder(BA type)

Model	A	H	D	Tool Size
TA12B41000-5040	200	346.8	∅ 80	□20(□3/4)
TA12B41000-5041	250	396.8	∅ 80	□20(□3/4)
TA12B41000-5042	300	446.8	∅ 80	□20(□3/4)
TA12B41000-5043	350	496.8	∅ 80	□20(□3/4)
TA12B41000-5050	200	346.8	∅ 110	□25(□1)
TA12B41000-5051	250	396.8	∅ 110	□25(□1)
TA12B41000-5052	300	446.8	∅ 110	□25(□1)
TA12B41000-5053	350	496.8	∅ 110	□25(□1)



● Boring tool holder(BP type)

Model	A	H	D	Tool Size
TA12B41000-5140	200	346.8	∅ 80	□20(□3/4)
TA12B41000-5141	250	396.8	∅ 80	□20(□3/4)
TA12B41000-5142	300	446.8	∅ 80	□20(□3/4)
TA12B41000-5143	350	496.8	∅ 80	□20(□3/4)
TA12B41000-5150	200	346.8	∅ 110	□25(□1)
TA12B41000-5151	250	396.8	∅ 110	□25(□1)
TA12B41000-5152	300	446.8	∅ 110	□25(□1)
TA12B41000-5153	350	496.8	∅ 110	□25(□1)





● Boring tool holder(BF type)

Model	A	H	D	Tool Size
TA12B41000-5240	200	346.8	∅ 80	□20(□3/4)
TA12B41000-5241	250	396.8	∅ 80	□20(□3/4)
TA12B41000-5242	300	446.8	∅ 80	□20(□3/4)
TA12B41000-5243	350	496.8	∅ 80	□20(□3/4)
TA12B41000-5250	200	346.8	∅ 110	□25(□1)
TA12B41000-5251	250	396.8	∅ 110	□25(□1)
TA12B41000-5252	300	446.8	∅ 110	□25(□1)
TA12B41000-5253	350	496.8	∅ 110	□25(□1)

Unit : mm (inch)

## VTB(C)-250




### ● Morse taper holde

Model No.	A	D	H	Tool Size
TL25-41701-5450	270	ø 85	421.8	MT # 5
TL25-41701-5460	345	ø 110	496.8	MT # 6
TL25-41701-5470	420	ø 130	571.8	MT # 7



### ● Square tool holder (Standard type)

Model No.	A	H	Tool Size
TL25-41701-0060	185	336.8	□ 50
TL25-41701-0061	235	336.8	□ 50
TL25-41701-0062	285	436.8	□ 50



### ● Boring tool holder (BA type)

Model No.	A	D	H	Tool Size
TL25-41701-5040	270	ø 130	421.8	□ 32
TL25-41701-5041	320	ø 130	471.8	□ 32
TL25-41701-5042	370	ø 130	521.8	□ 32
TL25-41701-5043	420	ø 130	571.8	□ 32





### ● Boring tool holder (BP type)

### ● Square tool holder (Through tool coolant)

Model No.	A	H	Tool Size
TL25-41701-0160	185	336.8	□ 50
TL25-41701-0161	235	336.8	□ 50
TL25-41701-0162	285	436.8	□ 50

Model No.	A	D	H	Tool Size
TL25-41701-5140	270	ø 130	421.8	□ 32
TL25-41701-5141	320	ø 130	471.8	□ 32
TL25-41701-5142	370	ø 130	521.8	□ 32
TL25-41701-5143	420	ø 130	571.8	□ 32



### ● Boring tool holder (BF type)

### ● Side lock holder

Model No.	A	D	H	Tool Size
TL25-41701-5350	220	ø 80	371.8	ø 40
TL25-41701-5360	220	ø 100	371.8	ø 50
TL25-41701-5370	245	ø 100	396.8	ø 60
TL25-41701-5380	295	ø 130	446.8	ø 80

Model No.	A	D	H	Tool Size
TL25-41701-5240	270	ø 130	421.8	□ 32
TL25-41701-5241	320	ø 130	471.8	□ 32
TL25-41701-5242	370	ø 130	521.8	□ 32
TL25-41701-5243	420	ø 130	571.8	□ 32





## CNC Vertical Boring & Turning Mills **VTB/VTC** Series Line-up




**VTB-100T**




**VTB(C)-100**



**VTB(C)-F series**



**VTB(C)-E series**




**VTB-V series**



**VTB(C)-APC**




**VTC-200E**



**VTC-250E**




**External Dimensions**



Unit:mm

MODEL	A	B	C	D	E	F	G	H	J (VTB-VTC)	K
VTB/VTC 100	3080	2735	5815	1530	4565	1300	515	785	4530/4790	800
125/140(E)	3600	3050	6650	1700	4335	1600	640	960	4790(5290)/5035(5535)	900
160(E)	3850	3240	7090	1855	4625	1900	740	1160	4790(5290)/5035(5535)	900
200E	4245	3630	7875	2450	6325	1500	100	1400	7260	1500
250E	4620	4540	9160	2650	6080	1700	100	1600	7710	1600





## Applications

### Wind Power Components



Gear Rim



Rotor Break Disk



Yaw Ring


### Valve & Pump Components



Valves



Valves



Pumps

### Industrial Components



Flange



Tube sheet



Self reinforced nozzle

### Vehicle Components



Aircraft engine impeller



Rail wheel



Ring gear

### Ship Components



Gear wheel supply unit



Intermediate wheel supply unit



Intermediate wheel



# HANKOOK

HEAD OFFICE & PLANT

**HANKOOK MACHINE TOOLS CO., LTD.**

42, Yeondeok-ro, Seongsan-gu, Changwon-si,  
Gyeongnam, 642-290 Korea

TEL: +82-55-282-7781/7660 FAX: +82-55-284-9791

E-mail: sales@hanmachine.com

[www.hanmachine.com](http://www.hanmachine.com)



AMERICA OFFICE

**Hankook America, Corp.**

1601 Atlantic Drive-#109 West Chicago, IL 60185 U.S.A

TEL: +1-630-562-9240 FAX: +1-630-562-9250

E-mail: hankookamerica@msn.com

EUROPE OFFICE

**Hankook Machine Germany GmbH**

Schwalbacher Str. 62

65760 Eschborn / Germany

TEL: +49-6196-99849-0 FAX: +49-6196-99849-29

E-mail: haller@hanmachine.de

[www.hanmachine.de](http://www.hanmachine.de)

北京代表处/BEIJING OFFICE

**韩国工作机械株式会社**

北京市朝阳区广顺南大街东亚望京中心B座1010室

Room 1010, Block B, Guangshun South Street,

East-Aisa Wangjing Center Building,

Chaoyang District, Beijing, 100102 China.

TEL: +86-10-8478-6108 FAX: +86-10-8478-6128

E-mail: wmh722@163.com

上海事务所/SHANGHAI OFFICE

**韩国工作机械株式会社**

上海市延安西路2299号世贸商城11P07

Room 11p07, Shanghai Mart, No.2299 West Yanan Rd.

Shanghai, China.

TEL: +86-21-6236-1153(Ext806) FAX: +86-21-6236-0323

E-mail: lgkim@126.com

JAPAN OFFICE

Maruei Nishihonmachi Bldg 4F,

1-15-16, Awaza, Nishi-ku, Osaka-shi 550-0011

TEL: +81-6-6543-3455 FAX: +81-6-6568-9255

E-mail: maki@hanmachine.com

hjkang@hanmachine.com

SINGAPORE OFFICE

**Hankook Singapore Pte. Ltd.**

Blk 1013 Geylang East Ave 3 #04-106 Singapore 389728.

TEL: +65-6747-8665 FAX: +65-6748-6546

E-mail: hanmachine@singnet.com.sg